

TFP SP – TFP SP RETINATO



MATERIAL

TFP SP – Plastified PVC flexible hose, with spring steel helix.
 TFP SP/RETINATO – Plastified PVC flexible hose with spring steel helix and polyester reinforcement.
 Weathering and chemicals resistant.

APPLICATION

TFP SP – Suction and delivery hose suitable to convey liquid foodstuffs. Food quality wall complies with D.M. dated 04/04/1985.
 TFP RETINATO – Suction and delivery hose suitable to convey liquid foodstuffs. Food quality wall complies with D.M. dated 04/04/1985

TEMPERATURE RANGE

-10 °C up to +60 °C

DELIVERY FORMS

TFP SP color: transparent
 TFP SP/RETINATO color: transparent

STANDARD LENGTHS

60m, 30m, 20 m (standard)

ON REQUEST

Other diameter, colors and lengths of production

TFP SP

				
Inner diameter (mm)	Weight (kg/m)	Working pressure (bar)	Vacuum (mm H ₂ O)	Length of coils (m)
8	0,150	12	85	60
10	0,165	12	85	60
12	0,180	10	85	60
14	0,205	10	85	60
16	0,245	8	85	60
18	0,300	8	85	60
20	0,350	7	85	60
22	0,380	7	85	60
25	0,510	7	85	60
30	0,600	5	85	60
32	0,150	5	85	60
35	0,165	5	85	60





TUBIFLESSIBILI

TFP SP

				
Inner diameter (mm)	Weight (kg/m)	Working pressure (bar)	Vacuum (mm H ₂ O)	Length of coils (m)
38	800	4	85	30
40	870	4	85	30
45	1100	4	80	30
50	1200	4	80	30
60	1700	4	80	30
63	1900	3	70	30
70	2400	3	70	30
76	2500	3	70	30
80	2700	3	70	30
90	3000	3	70	30
102	3400	2	70	30
110	3950	2	70	30
120	4300	2	70	20
127	4700	2	70	20
153	6500	2	60	20

TFP SP RETINATO

				
Inner diameter (mm)	Weight (kg/m)	Working pressure (bar)	Vacuum (mm H ₂ O)	Length of coils (m)
12	0,180	15	85	60
14	0,205	15	85	60
16	0,245	15	85	60
18	0,300	12	85	60
20	0,350	12	85	60
22	0,380	11	85	60
25	0,510	11	85	60
30	0,600	10	85	60
32	0,680	10	85	60
35	0,750	9	85	60
38	0,800	9	85	30
40	0,870	9	85	30
45	1,100	7	80	30
50	1,200	7	80	30
60	1,700	6	80	30

