

ONDASIL1 - POLI



STRUCTURE

Silicone hump hoses made of VMQ (Vinyl Methyl Quality) silicone, with polyester reinforcement. Possibility to be supplied with Fluorosilicone liner (FVMQ) or silicone oil resistant, and/or aramidic fibres reinforcements (Nomex®, Kevlar®, etc.)

TEMPERATURE RANGE

-55 °C up to +180°C with peaks to +200 °C

COLOUR

Blue, other on request

APPLICATION

Cooling systems for passenger cars, motorbikes, excavators, industrial vehicles, buses and general industrial systems. Turbocharger and intercooler systems

							
Article ID	Inner diameter (mm)	Wall thickness (mm)	Reinforcement number	Wall thickness tolerance (mm)	Burst pressure (bar)	Hardness (Shore A)	Length (mm)
SBP1ON04500010G	45	4,5	3	+1 / -0,5	14	65 - 75	102
SBP1ON05100010G	51	5	4	+1 / -0,5	14	65 - 75	102
SBP1ON05800010G	58	5	4	+1 / -0,5	12	65 - 75	102
SBP1ON06000010G	60	5	4	+1 / -0,5	10	65 - 75	102
SBP1ON06300010G	63	5	4	+1 / -0,5	10	65 - 75	102
SBP1ON07000010G	70	5	4	+1 / -0,5	8	65 - 75	102
SBP1ON07600510G	76	5,5	5	+1 / -0,5	8	65 - 75	102
SBP1ON08000510G	80	5,5	5	+1 / -0,5	8	65 - 75	102
SBP1ON09000010G	90	5,5	5	+1 / -0,5	5,5	65 - 75	102
SBP1ON10200010G	102	5,5	5	+1 / -0,5	5	65 - 75	102

