



TUBIFLESSIBILI

TFN1



MATERIAL

Single ply neoprene coated both sides fiberglass cloth internal wire and single external glass tension cord

APPLICATION

This extremely light-weight flexible ducting is excellent for the distribution and extraction of air, fumes and light powders where high temperatures are present

TEMPERATURE RANGE

- 45 °C / +125 °C, peaks of 150 °C

COLOUR

Black, white cord

STANDARD LENGTHS:

4 meters

NOTES:

It is possible to supply the hose in cutted lengths, with cuffed ends, without metal wire for an easy connection or eventually enlarged

				
Article ID	Inner diameter (mm)	Bending radius (mm)	Working pressure (bar)	Vacuum (mm H ₂ O)
TFN10013-0000B	13	7	1,5	5300
TFN10016-0000B	16	7	1,5	5300
TFN10018-0000B	18	9	1,5	5300
TFN10019-0000B	19	9	1,5	5300
TFN10022-0000B	22	11	1,5	5300
TFN10025-0000B	25	12	1,4	5300
TFN10028-0000B	28	13	1,4	5000
TFN10030-0000B	30	15	1,4	5000
TFN10032-0000B	32	16	1,4	5000
TFN10035-0000B	35	17	1,4	5000
TFN10038-0000B	38	19	1,4	5000
TFN10040-0000B	40	21	1,3	5000
TFN10042-0000B	42	22	1,2	4400





TUBIFLESSIBILI

				
Article ID	Inner diameter (mm)	Bending radius (mm)	Working pressure (bar)	Vacuum (mm H ₂ O)
TFN10045-0000B	45	22	1,2	4400
TFN10051-0000B	51	25	1,2	4400
TFN10055-0000B	55	26	1,1	4000
TFN10057-0000B	57	28	1,1	4000
TFN10060-0000B	60	29	1,1	4000
TFN10063-0000B	63	31	1,1	4000
TFN10065-0000B	65	33	1,1	3500
TFN10070-0000B	70	35	1,1	3500
TFN10076-0000B	76	38	1,1	3500
TFN10080-0000B	80	40	1,1	3000
TFN10083-0000B	83	41	1,1	3000
TFN10090-0000B	90	44	0,9	2950
TFN10095-0000B	95	47	0,9	2700
TFN10102-0000B	102	51	0,9	2600
TFN10108-0000B	108	54	0,8	2300
TFN10110-0000B	110	55	0,8	2100
TFN10114-0000B	114	57	0,8	2100
TFN10120-0000B	120	60	0,8	1900
TFN10127-0000B	127	63	0,8	1700
TFN10130-0000B	130	65	0,8	1700
TFN10140-0000B	140	70	0,8	1500
TFN10152-0000B	152	76	0,6	1400
TFN10160-0000B	160	80	0,6	1200
TFN10165-0000B	165	86	0,6	1000
TFN10178-0000B	178	88	0,6	1000
TFN10180-0000B	180	90	0,6	1000
TFN10185-0000B	185	95	0,5	900
TFN10203-0000B	203	101	0,5	700
TFN10230-0000B	230	114	0,4	600
TFN10254-0000B	254	127	0,4	500
TFN10305-0000B	305	152	0,1	300

