

TFP SP PUR 0.4



MATERIAL

Hose in polyurethane ester spiral reinforcement harmonic galvanized steel or copper. The thickness of 0.40 mm makes the tube very lightweight and flexible. Excellent mechanical properties, resistant to abrasion, cold, aging and to many chemicals. Absence of PVC and halogen

TEMPERATURE RANGE

From -40 °C to +90 °C.

COLOUR

Transparent

APPLICATION

Suitable aspirations and blowing dust, fumes, sawdust, shavings minor, etc.

						
Article ID	Inner diameter (mm)	Weight (g/m)	Bending radius (mm)	Working pressure (mbar)	Vacuum (mbar)	Length (m)
TFPSPPUR050	50	230	13	400	18	20
TFPSPPUR060	60	275	17	394	16	20
TFPSPPUR070	70	320	20	345	15	20
TFPSPPUR076	76	345	22	295	14	20
TFPSPPUR080	80	320	23	266	10	20
TFPSPPUR090	90	405	26	226	10	20
TFPSPPUR100	100	450	29	197	10	20
TFPSPPUR110	110	480	31	197	9	20
TFPSPPUR120	120	490	34	187	9	20
TFPSPPUR125	125	505	36	187	9	20





TUBIFLESSIBILI

						
Article ID	Inner diameter (mm)	Weight (g/m)	Bending radius (mm)	Working pressure (mbar)	Vacuum (mbar)	Length (m)
TFPSPPUR130	130	525	37	177	8	20
TFPSPPUR140	140	630	40	148	8	20
TFPSPPUR150	150	670	43	108	8	20
TFPSPPUR160	160	715	46	98	6	20
TFPSPPUR180	180	835	51	89	6	20
TFPSPPUR200	200	925	57	89	5	20
TFPSPPUR225	225	1035	64	79	5	10
TFPSPPUR250	250	1150	71	49	4	10
TFPSPPUR275	275	1675	79	30	3	10
TFPSPPUR300	300	1815	86	30	3	10

