

TFP SP PUR 0.4R



MATERIAL

Hose in polyurethane ester spiral reinforcement harmonic galvanized steel or copper. The thickness of 0.40 mm makes the tube very lightweight and flexible. Excellent mechanical properties, resistant to abrasion, cold, aging and to many chemicals. Absence of PVC and halogen

TEMPERATURE RANGE

From -40 °C to +90 °C.

COLOUR

Transparent

APPLICATION

Suitable aspirations and blowing dust, fumes, sawdust, shavings minor, etc.

						
Article ID	Inner diameter (mm)	Weight (g/m)	Bending radius (mm)	Working pressure (mbar)	Vacuum (mbar)	Length (m)
TFPSPPUR050R	50	210	25	400	40	20
TFPSPPUR060R	60	265	30	380	40	20
TFPSPPUR070R	70	335	35	345	35	20
TFPSPPUR076R	76	360	38	305	35	20
TFPSPPUR080R	80	365	40	285	30	20
TFPSPPUR090R	90	405	45	240	30	20
TFPSPPUR100R	100	450	50	210	25	20
TFPSPPUR110R	110	495	55	210	25	20
TFPSPPUR120R	120	535	60	200	20	20
TFPSPPUR125R	125	555	63	200	20	20





TUBIFLESSIBILI

						
Article ID	Inner diameter (mm)	Weight (g/m)	Bending radius (mm)	Working pressure (mbar)	Vacuum (mbar)	Length (m)
TFPSPPUR130R	130	580	65	190	20	20
TFPSPPUR140R	140	700	70	160	15	20
TFPSPPUR150R	150	750	75	120	15	20
TFPSPPUR160R	160	795	80	105	15	20
TFPSPPUR180R	180	890	90	95	10	20
TFPSPPUR200R	200	990	100	95	10	20
TFPSPPUR225R	225	1115	113	85	10	10
TFPSPPUR250R	250	1235	125	50	10	10
TFPSPPUR275R	275	1840	139	30	10	10
TFPSPPUR300R	300	1990	150	30	10	10

