



TUBIFLESSIBILI

TFP SP PUR 0.6



MATERIAL

Hose in polyurethane ester with a 0.60 mm wall reinforced by a harmonic spiral of galvanized steel or copper. Excellent mechanical properties, resistant to abrasion, cold, aging and many chemicals. Absence of PVC and halogen

TEMPERATURE RANGE

From -40 °C to +90 °C with peaks up to 120 °C

COLOUR

Transparent

APPLICATION

Suitable aspirations and blowing dust, fumes, sawdust, shavings minor, etc.

						
Article ID	Weight (g/m)	Bending radius (mm)	Working pressure (mbar)	Vacuum (mbar)	Length (m)	Lunghezza (m)
TFPSPHPUR050	50	340	35	880	190	20
TFPSPHPUR060	60	415	45	840	170	20
TFPSPHPUR070	70	480	50	740	160	20
TFPSPHPUR076	76	520	55	640	150	20
TFPSPHPUR080	80	545	60	570	120	20
TFPSPHPUR090	90	525	65	490	110	20
TFPSPHPUR100	100	645	70	430	110	20
TFPSPHPUR110	110	705	80	420	100	20
TFPSPHPUR120	120	850	85	400	100	20
TFPSPHPUR125	125	885	90	400	100	20





TUBIFLESSIBILI

						
Article ID	Weight (g/m)	Bending radius (mm)	Working pressure (mbar)	Vacuum (mbar)	Length (m)	Lunghezza (m)
TFPSPHPUR130	130	920	95	380	90	20
TFPSPHPUR140	140	990	100	320	90	20
TFPSPHPUR150	150	1055	110	130	80	20
TFPSPHPUR160	160	1225	115	210	80	20
TFPSPHPUR180	180	1230	130	190	60	20
TFPSPHPUR200	200	1365	145	190	50	20
TFPSPHPUR225	225	1530	160	170	50	10
TFPSPHPUR250	250	1695	180	110	40	10
TFPSPHPUR275	275	2170	200	65	30	10
TFPSPHPUR300	300	2300	215	65	30	10

