



TUBIFLESSIBILI

TFS1



MATERIAL

Single ply silicone coated both sides fiberglass cloth internal wire and single external glass tension cord

APPLICATION

This extremely light-weight flexible ducting is excellent for the distribution and extraction of air, fumes and light powders where high temperatures are present

TEMPERATURE RANGE

-65 °C / +260 °C, peaks of 300 °C

COLOUR

Red, white cord

STANDARD LENGTHS:

4 meters

NOTES:

It is possible to supply the hose in cutted lengths, with cuffed ends, without metal wire for an easy connection or eventually enlarged

				
Article ID	Inner diameter (mm)	Bending radius (mm)	Working pressure (bar)	Vacuum (mm H ₂ O)
TFS10013-0000B	13	9	1,5	5300
TFS10016-0000B	16	9	1,5	5300
TFS10019-0000B	19	9	1,5	5300
TFS10022-0000B	22	11	1,5	5300
TFS10025-0000B	25	12	1,4	5300
TFS10028-0000B	28	13	1,4	5000
TFS10030-0000B	30	15	1,4	5000
TFS10032-0000B	32	16	1,4	5000
TFS10035-0000B	35	17	1,4	5000
TFS10038-0000B	38	19	1,4	5000
TFS10040-0000B	40	21	1,3	5000
TFS10042-0000B	42	22	1,2	4400
TFS10045-0000B	45	22	1,2	4400

Tubi Flessibili S.r.l. - Tel: +39 0131238971 - Email: info@tubiflessibili.net

Copyright © TUBI FLESSIBILI S.r.l. - All rights reserved. The texts and images are property of Tubi Flessibili S.r.l. Even partial reproduction of the catalog is prohibited.





TUBIFLESSIBILI

				
Article ID	Inner diameter (mm)	Bending radius (mm)	Working pressure (bar)	Vacuum (mm H ₂ O)
TFS10051-0000B	51	25	1,2	4400
TFS10055-0000B	55	26	1,1	4000
TFS10057-0000B	57	28	1,1	4000
TFS10060-0000B	60	29	1,1	4000
TFS10063-0000B	63	31	1,1	4000
TFS10065-0000B	65	33	1,1	3500
TFS10070-0000B	70	35	1,1	3500
TFS10076-0000B	76	38	1,1	3500
TFS10080-0000B	80	40	1,1	3000
TFS10083-0000B	83	41	1,1	3000
TFS10090-0000B	90	44	0,9	2950
TFS10095-0000B	95	47	0,9	2700
TFS10102-0000B	102	51	0,9	2600
TFS10108-0000B	108	54	0,8	2300
TFS10110-0000B	110	55	0,8	2100
TFS10114-0000B	114	57	0,8	2100
TFS10120-0000B	120	60	0,8	1900
TFS10127-0000B	127	63	0,8	1700
TFS10130-0000B	130	65	0,8	1700
TFS10140-0000B	140	70	0,8	1500
TFS10152-0000B	152	76	0,6	1400
TFS10160-0000B	160	80	0,6	1200
TFS10165-0000B	165	86	0,6	1000
TFS10178-0000B	178	90	0,6	1000
TFS10180-0000B	180	95	0,5	900
TFS10203-0000B	203	101	0,5	700
TFS10230-0000B	230	114	0,4	600
TFS10254-0000B	254	127	0,4	500
TFS10305-0000B	305	152	0,1	300

