



TUBIFLESSIBILI

TFS2



MATERIAL

Double ply silicone coated both sides fiberglass cloth, internal wire and double external glass tension cord

APPLICATION

This extremely light-weight flexible ducting is excellent for the distribution and extraction of air, fumes and light powders where high temperatures are present

TEMPERATURE RANGE

-65 °C / +260 °C, peaks of 300 °C

COLOUR

Red, white/yellow cord

STANDARD LENGTHS:

4 meters

NOTES:

It is possible to supply the hose in cutted lengths, with cuffed ends, without metal wire for an easy connection or eventually enlarged

				
Article ID	Inner diameter (mm)	Bending radius (mm)	Working pressure (bar)	Vacuum (mm H ₂ O)
TFS20013-0000B	13	13	2,50	7000
TFS20016-0000B	16	16	2,50	7000
TFS20019-0000B	19	19	2,50	7000
TFS20022-0000B	22	22	2,50	7000
TFS20025-0000B	25	25	2,50	7000
TFS20028-0000B	28	28	2,50	5800
TFS20030-0000B	30	30	2,50	5800
TFS20032-0000B	32	32	2,50	5800
TFS20035-0000B	35	35	2,40	5800
TFS20038-0000B	38	38	2,40	5800
TFS20040-0000B	40	40	2,40	5800
TFS20042-0000B	42	42	2,40	5800
TFS20045-0000B	45	45	2,40	5800

Tubi Flessibili S.r.l. - Tel: +39 0131238971 - Email: info@tubiflessibili.net

Copyright © TUBI FLESSIBILI S.r.l. - All rights reserved. The texts and images are property of Tubi Flessibili S.r.l. Even partial reproduction of the catalog is prohibited.





TUBIFLESSIBILI

				
Article ID	Inner diameter (mm)	Bending radius (mm)	Working pressure (bar)	Vacuum (mm H ₂ O)
TFS20051-0000B	51	51	2,40	5300
TFS20055-0000B	55	55	2,30	5300
TFS20057-0000B	57	57	2,30	5300
TFS20060-0000B	60	60	2,20	4600
TFS20063-0000B	63	63	2,20	4600
TFS20065-0000B	65	65	2,20	4600
TFS20070-0000B	70	70	2,20	4600
TFS20076-0000B	76	76	2,10	4400
TFS20080-0000B	80	80	2,10	4000
TFS20083-0000B	83	83	2,10	4000
TFS20090-0000B	90	90	2,10	4000
TFS20095-0000B	95	95	2,00	4000
TFS20102-0000B	102	102	1,80	3500
TFS20110-0000B	110	110	1,80	3000
TFS20114-0000B	114	114	1,70	2800
TFS20120-0000B	120	120	1,60	2300
TFS20127-0000B	127	127	1,50	2100
TFS20130-0000B	130	130	1,40	1800
TFS20140-0000B	140	140	1,40	1800
TFS20152-0000B	152	152	1,10	1700
TFS20160-0000B	160	160	0,90	1500
TFS20165-0000B	165	165	0,80	1400
TFS20178-0000B	178	178	0,80	1400
TFS20180-0000B	180	180	0,80	1100
TFS20185-0000B	185	185	0,70	1100
TFS20203-0000B	203	203	0,60	1000
TFS20230-0000B	230	230	0,50	800
TFS20254-0000B	254	254	0,40	700
TFS20305-0000B	305	305	0,20	500

