

TUBOSIL - FKM/NMX



MATERIAL

VMQ (Vinyl Methyl Quality) silicone hoses with aramidic textile reinforcements and fluorinated elastomers underlay (FKM)

TEMPERATURE RANGE

-30°C up to +230°C

APPLICATION

Connection between turbine and intercooler on cars, trucks, industrial vehicles and generators, for the passage of petrol, oils and aggressive chemicals

COLOUR

Green (RAL6038) with black interior

							
Article ID	Inner diameter (mm)	Wall thickness (mm)	Reinforcement number	Wall thickness tolerance (mm)	Burst pressure (bar)	Hardness (Shore A)	Length (mm)
SFK00000650000G	6,5	4,0	3	+1 / -0,5	45	65 - 75	1000 or 4000
SFK00000800000G	8	4,0	3	+1 / -0,5	45	65 - 75	1000 or 4000
SFK00000950000G	9,5	4,0	3	+1 / -0,5	35	65 - 75	1000 or 4000
SFK00001100000G	11	4,0	3	+1 / -0,5	35	65 - 75	1000 or 4000
SFK00001300000G	13	4,0	3	+1 / -0,5	35	65 - 75	1000 or 4000
SFK00001600000G	16	4,0	3	+1 / -0,5	30	65 - 75	1000 or 4000
SFK00001900000G	19	4,0	3	+1 / -0,5	28	65 - 75	1000 or 4000
SFK00002200000G	22	4,0	3	+1 / -0,5	19,3	65 - 75	1000 or 4000
SFK00002500000G	25	4,0	3	+1 / -0,5	19,3	65 - 75	1000 or 4000
SFK00002800000G	28	4,5	3	+1 / -0,5	19,3	65 - 75	1000 or 4000
SFK00003000000G	30	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000
SFK00003200000G	32	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000
SFK00003500000G	35	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000





TUBIFLESSIBILI

							
Article ID	Inner diameter (mm)	Wall thickness (mm)	Reinforcement number	Wall thickness tolerance (mm)	Burst pressure (bar)	Hardness (Shore A)	Length (mm)
SFK00003800000G	38	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000
SFK00004000000G	40	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000
SFK00004200000G	42	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000
SFK00004500000G	45	4,5	3	+1 / -0,5	14	65 - 75	1000 or 4000
SFK00004800000G	48	4,5	3	+1 / -0,5	14	65 - 75	1000 or 4000
SFK00005100000G	51	5,0	4	+1 / -0,5	14	65 - 75	1000 or 4000
SFK00005300000G	53	5,0	4	+1 / -0,5	14	65 - 75	1000 or 4000
SFK00005500000G	55	5,0	4	+1 / -0,5	13	65 - 75	1000 or 4000
SFK00005700000G	57	5,0	4	+1 / -0,5	12	65 - 75	1000 or 4000
SFK00006000000G	60	5,0	4	+1 / -0,5	10	65 - 75	1000 or 4000
SFK00006300000G	63	5,0	4	+1 / -0,5	10	65 - 75	1000 or 4000
SFK00006500000G	65	5,0	4	+1 / -0,5	10	65 - 75	1000 or 4000
SFK00006800000G	68	5,0	4	+1 / -0,5	8	65 - 75	1000 or 4000
SFK00007000000G	70	5,0	4	+1 / -0,5	8	65 - 75	1000 or 4000
SFK00007600000G	76	5,5	4	+1 / -0,5	8	65 - 75	1000 or 4000
SFK00008000000G	80	5,5	5	+1 / -0,5	8	65 - 75	1000 or 4000
SFK00008300000G	83	5,5	5	+1 / -0,5	5,5	65 - 75	1000 or 4000
SFK00009000000G	90	5,5	5	+1 / -0,5	5,5	65 - 75	1000 or 4000
SFK00010200000G	102	5,5	5	+1 / -0,5	5	65 - 75	1000 or 4000
SFK00011400000G	114	5,5	5	+1 / -0,5	5	65 - 75	1000 or 4000
SFK00012000000G	120	5,5	5	+1 / -0,5	5	65 - 75	1000 or 4000
SFK00012700000G	127	5,5	5	+1 / -0,5	5	65 - 75	1000 or 4000
SFK00015200000G	152	5,5	5	+1 / -0,5	5	65 - 75	1000 or 4000

Tubi Flessibili S.r.l. - Tel: +39 0131238971 - Email: info@tubiflessibili.net

According to ISO 1307/ SAE J20

Above technical data are referring to applications at a room temperature (+20°C)

Copyright © TUBI FLESSIBILI S.r.l. - All rights reserved. The texts and images are property of Tubi Flessibili S.r.l.
Even partial reproduction of the catalog is prohibited.

