



TUBIFLESSIBILI

TUBOSIL - POLI



STRUCTURE

Straight hoses made of VMQ (Vinyl Methyl Quality) silicone, with polyester reinforcement. Can be supplied with Fluorosilicone (FVMQ) inner layer

TEMPERATURE RANGE

-55 °C / +180 °C with peaks to + 200 °C

COLOUR

Blue, other on request

APPLICATION

Cooling systems for passenger cars, motorbikes, excavators, industrial vehicles, buses and general industrial systems. Turbocharger and intercooler systems

							
Article ID	Inner diameter (mm)	Wall thickness (mm)	Reinforcement number	Wall thickness tolerance (mm)	Burst pressure (bar)	Hardness (Shore A)	Length (mm)
SBP00000600000G	6,5	4,0	3	+1 / -0,5	45	65 - 75	1000 or 4000
SBP00000800000G	8	4,0	3	+1 / -0,5	45	65 - 75	1000 or 4000
SBP00001000000G	9,5	4,0	3	+1 / -0,5	35	65 - 75	1000 or 4000
SBP00001100000G	11	4,0	3	+1 / -0,5	35	65 - 75	1000 or 4000
SBP00001300000G	13	4,0	3	+1 / -0,5	35	65 - 75	1000 or 4000
SBP00001600000G	16	4,0	3	+1 / -0,5	30	65 - 75	1000 or 4000
SBP00001900000G	19	4,0	3	+1 / -0,5	28	65 - 75	1000 or 4000
SBP00002200000G	22	4,0	3	+1 / -0,5	19,3	65 - 75	1000 or 4000
SBP00002500000G	25	4,0	3	+1 / -0,5	19,3	65 - 75	1000 or 4000
SBP00002800000G	28	4,5	3	+1 / -0,5	19,3	65 - 75	1000 or 4000
SBP00003000000G	30	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000
SBP00003200000G	32	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000

Tubi Flessibili S.r.l. - Tel: +39 0131238971 - Email: info@tubiflessibili.net

According to ISO 1307/ SAE J20

Above technical data are referring to applications at a room temperature (+20°C)

Copyright © TUBI FLESSIBILI S.r.l. - All rights reserved. The texts and images are property of Tubi Flessibili S.r.l.
Even partial reproduction of the catalog is prohibited.





TUBIFLESSIBILI

							
Article ID	Inner diameter (mm)	Wall thickness (mm)	Reinforcement number	Wall thickness tolerance (mm)	Burst pressure (bar)	Hardness (Shore A)	Length (mm)
SBP00003500000G	35	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000
SBP00003800000G	38	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000
SBP00004000000G	40	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000
SBP00004200000G	42	4,5	3	+1 / -0,5	15,4	65 - 75	1000 or 4000
SBP00004500000G	45	4,5	3	+1 / -0,5	14	65 - 75	1000 or 4000
SBP00004800000G	48	4,0	3	+1 / -0,5	14	65 - 75	1000 or 4000
SBP00005100000G	51	5,0	4	+1 / -0,5	14	65 - 75	1000 or 4000
SBP00005300000G	53	5,0	4	+1 / -0,5	14	65 - 75	1000 or 4000
SBP00005500000G	55	5,0	4	+1 / -0,5	13	65 - 75	1000 or 4000
SBP00005700000G	57	5,0	4	+1 / -0,5	12	65 - 75	1000 or 4000
SBP00006000000G	60	5,0	4	+1 / -0,5	10	65 - 75	1000 or 4000
SBP00006300000G	63	5,0	4	+1 / -0,5	10	65 - 75	1000 or 4000
SBP00006500000G	65	5,0	4	+1 / -0,5	10	65 - 75	1000 or 4000
SBP00006800000G	68	5,0	4	+1 / -0,5	8	65 - 75	1000 or 4000
SBP00007000000G	70	5,0	4	+1 / -0,5	8	65 - 75	1000 or 4000
SBP00007600000G	76	5,5	5	+1 / -0,5	8	65 - 75	1000 or 4000
SBP00008000000G	80	5,5	5	+1 / -0,5	8	65 - 75	1000 or 4000
SBP00008300000G	83	5,5	5	+1 / -0,5	5,5	65 - 75	1000 or 4000
SBP00009000000G	90	5,5	5	+1 / -0,5	5,5	65 - 75	1000 or 4000
SBP00010200000G	102	5,5	5	+1 / -0,5	5	65 - 75	1000 or 4000
SBP00011400000G	114	5,5	5	+1 / -0,5	5	65 - 75	1000 or 4000
SBP00012000000G	120	5,5	5	+1 / -0,5	5	65 - 75	1000 or 4000
SBP00012700000G	127	5,5	5	+1 / -0,5	5	65 - 75	1000 or 4000
SBP00015200000G	152	5,5	5	+1 / -0,5	5	65 - 75	1000 or 4000

Tubi Flessibili S.r.l. - Tel: +39 0131238971 - Email: info@tubiflessibili.net

According to ISO 1307/ SAE J20

Above technical data are referring to applications at a room temperature (+20°C)

Copyright © TUBI FLESSIBILI S.r.l. - All rights reserved. The texts and images are property of Tubi Flessibili S.r.l.
Even partial reproduction of the catalog is prohibited.

