

TUBOSIL TRECCIATO R/B



MATERIAL

VMQ (Vinyl Methyl Quality) silicone hoses, polyester textile reinforcements

APPLICATION

Connections between radiators and engines, for passenger cars, lorries, industrial vehicles, power generators, for conveying of cooling liquids and antifreeze

TEMPERATURE RANGE

-60 °C up to +180°C with +200 °C peak

COLOUR

Blue external, red internal

STANDARD LENGTH

25 meters, others on request

CHARATERISTICS

Meets and exceeds SAE J 20 R1 class A

						
Article ID	Inner diameter (mm)	Wall thickness (mm)	Reinforcement number	Burst pressure (bar)	Hardness (Shore A)	Roll lenght (m)
TUSILTX.R/B06GT	6	4,0	1	17,5	65-75	25
TUSILTX.R/B08GT	8	4,0	1	17,5	65-75	25
TUSILTX.R/B10GT	10	4,0	1	17,5	65-75	25
TUSILTX.R/B13GT	13	4,0	1	17,5	65-75	25
TUSILTX.R/B16GT	16	4,0	1	17,5	65-75	25
TUSILTX.R/B19GT	19	4,0	1	14	65-75	25
TUSILTX.R/B22GT	22	5,0	1	12	65-75	25
TUSILTX.R/B25GT	25	5,0	1	12	65-75	25
TUSILTX.R/B28GT	28	5,0	1	12	65-75	25
TUSILTX.R/B30GT	30	5,5	1	12	65-75	25
TUSILTX.R/B32GT	32	5,5	1	12	65-75	25

