



TUBIFLESSIBILI

TUBOSIL - VMQ/NMX



MATERIAL

VMQ (Vinyl Methyl Quality) silicone hoses with aramidic textile reinforcements

APPLICATION

Connections between radiators and engines, between turbo-charger and intercooler for passenger cars, lorries, industrial vehicles, power generators, for conveying of cooling liquids, antifreeze and/or hot air

TEMPERATURE RANGE

-60 °C up to +225 °C with peaks to +250°C

COLOUR

Red iron oxide

							
Article ID	Inner diameter (mm)	Wall thickness (mm)	Reinforcement number	Wall thickness tolerance (mm)	Burst pressure (bar)	Hardness (Shore A)	Length (mm)
SON00000600000G	6,5	4,0	3	+1 / -0,5	45	65 - 75	1000 v 4000
SON00000800000G	8	4,0	3	+1 / -0,5	45	65 - 75	1000 v 4000
SON00000900000G	9,5	4,0	3	+1 / -0,5	35	65 - 75	1000 v 4000
SON00001100000G	11	4,0	3	+1 / -0,5	35	65 - 75	1000 v 4000
SON00001300000G	13	4,0	3	+1 / -0,5	35	65 - 75	1000 v 4000
SON00001600000G	16	4,0	3	+1 / -0,5	30	65 - 75	1000 v 4000
SON00001900000G	19	4,0	3	+1 / -0,5	28	65 - 75	1000 v 4000
SON00002200000G	22	4,0	3	+1 / -0,5	19,3	65 - 75	1000 v 4000
SON00002500000G	25	4,0	3	+1 / -0,5	19,3	65 - 75	1000 v 4000
SON00002800000G	28	4,5	3	+1 / -0,5	19,3	65 - 75	1000 v 4000
SON00003000000G	30	4,5	3	+1 / -0,5	15,4	65 - 75	1000 v 4000
SON00003200000G	32	4,5	3	+1 / -0,5	15,4	65 - 75	1000 v 4000

Tubi Flessibili S.r.l. - Tel: +39 0131238971 - Email: info@tubiflessibili.net

According to ISO 1307/ SAE J20

Above technical data are referring to applications at a room temperature (+20°C)

Copyright © TUBI FLESSIBILI S.r.l. - All rights reserved. The texts and images are property of Tubi Flessibili S.r.l.
Even partial reproduction of the catalog is prohibited.





TUBIFLESSIBILI

							
Article ID	Inner diameter (mm)	Wall thickness (mm)	Reinforcement number	Wall thickness tolerance (mm)	Burst pressure (bar)	Hardness (Shore A)	Length (mm)
SON00003500000G	35	4,5	3	+1 / -0,5	15,4	65 - 75	1000 v 4000
SON00003800000G	38	4,5	3	+1 / -0,5	15,4	65 - 75	1000 v 4000
SON00004000000G	40	4,5	3	+1 / -0,5	15,4	65 - 75	1000 v 4000
SON00004200000G	40	4,5	3	+1 / -0,5	15,4	65 - 75	1000 v 4000
SON00004500000G	45	4,5	3	+1 / -0,5	14	65 - 75	1000 v 4000
SON00004800000G	48	4,5	3	+1 / -0,5	14	65 - 75	1000 v 4000
SON00005100000G	51	5,0	4	+1 / -0,5	14	65 - 75	1000 v 4000
SON00005300000G	53	5,0	4	+1 / -0,5	14	65 - 75	1000 v 4000
SON00005500000G	55	5,0	4	+1 / -0,5	13	65 - 75	1000 v 4000
SON00005700000G	57	5,0	4	+1 / -0,5	12	65 - 75	1000 v 4000
SON00006000000G	60	5,0	4	+1 / -0,5	10	65 - 75	1000 v 4000
SON00006300000G	63	5,0	4	+1 / -0,5	10	65 - 75	1000 v 4000
SON00006500000G	65	5,0	4	+1 / -0,5	10	65 - 75	1000 v 4000
SON00006800000G	68	5,0	4	+1 / -0,5	8	65 - 75	1000 v 4000
SON00007000000G	70	5,0	4	+1 / -0,5	8	65 - 75	1000 v 4000
SON00007600000G	76	5,0	4	+1 / -0,5	8	65 - 75	1000 v 4000
SON00008000000G	80	5,0	4	+1 / -0,5	8	65 - 75	1000 v 4000
SON00008300000G	83	5,0	4	+1 / -0,5	5,5	65 - 75	1000 v 4000
SON00009000000G	90	5,0	4	+1 / -0,5	5,5	65 - 75	1000 v 4000
SON00010200000G	102	5,0	4	+1 / -0,5	5	65 - 75	1000 v 4000
SON00011400000G	114	5,0	4	+1 / -0,5	5	65 - 75	1000 v 4000
SON00012000000G	129	5,0	4	+1 / -0,5	5	65 - 75	1000 v 4000
SON00012700000G	127	5,0	4	+1 / -0,5	5	65 - 75	1000 v 4000
SON00015200000G	152	5,0	4	+1 / -0,5	5	65 - 75	1000 v 4000

Tubi Flessibili S.r.l. - Tel: +39 0131238971 - Email: info@tubiflessibili.net

According to ISO 1307/ SAE J20

Above technical data are referring to applications at a room temperature (+20°C)

Copyright © TUBI FLESSIBILI S.r.l. - All rights reserved. The texts and images are property of Tubi Flessibili S.r.l.
Even partial reproduction of the catalog is prohibited.

