



TUBI E MANICOTTI STANDARD COSTRUITI SU MANDRINO RIGIDO SECONDO ISO 1307

	
Diametro nominale (mm)	Tolleranza (mm)
3,2	-0/+0,6
4,0	-0/+0,8
5,0	±0,4
6,3	-0,1/+0,7
8,0	-0,3/+0,5
10,0	-0,7/+0,1
12,5	-0,2/+1
16,0	-0,5/+0,7
19,0	-0,4/+0,8
20,0	-0,4/+0,8
25,0	-0/+1,4
31,5	-0,1/+1,5
38,0	-0,3/+1,3
40,0	-0,3/+1,3
50,0	-0,6/+1
51,0	-0,6/+1
63,0	+0,1/+2,1
76,0	-1,4/+1,8
80,0	-1,4/+1,8
100,0	-0/+3,2
125,0	+0,4/+3,6
150,0	+0,4/+4,4
200,0	+0,7/+5,7
250,0	+1/+7
315,0	-0,5/+5,5

TUBI E MANICOTTI STANDARD COSTRUITI SU MANDRINO RIGIDO SECONDO ISO 1307

	
Lunghezza nominale (mm)	Tolleranza (mm)
≤ 300	±3,00
> 300 a ≤ 600	±4,50
> 600 a ≤ 900	±6,00
> 900 a ≤ 1200	±9,00
> 1200 a ≤ 1800	±12,00
> 1800	±1%

TUBI E MANICOTTI STANDARD COSTRUITI SU MANDRINO RIGIDO SECONDO ISO 1307

	
Spessore parete (mm)	Tolleranza (mm)
Da 0 a 3,00	-0,5 / +1,00
Da 3,01 a 5,00	-0,5 / +1,00
Da 5,01 a 7,00	-0,5 / +1,00
Da 7,01 a 10,00	-0,5 / +1,00
> 10,00	-0,5 / +1,00

